

FSTB Installation

- This guide provides installation instructions for the Front Strut Tower Brace.

Tools Required

- Ratchet
- 12mm Socket
- Torque Wrench

Installation Notes


It is best to have the car on a flat, level surface for the installation of this brace.

Steps

- I. Start by loosening the bolts on each strut tower (3x).



II. Leave the large C spacer in place.



III. Place the FSTB in place with the Cross Bar and welds facing up. It may fit rather snug so push one side down a few threads, then the other equally. Repeat this until you walk each side to the bottom of the threads. This may require lateral movement of the car and/or brace to achieve (slightly rock the car by the fender). Take special care not to hammer the brace down, thus potentially damaging the threads of the bolts.



IV. Hand thread the nuts back on to the bolts of each strut tower (6x).

V. Tighten firmly with a ratchet and 12mm socket (6x).

VI. Torque to 29 ft/lbs (6x).

Typical Order of Installation

- FSTB
- RSTB
- BP or MSMB
- FMB
- RLCB
- RMB

DISCLAIMER

Proper service and repair procedures are vital to the safe, reliable operation of all motor vehicles as well as the personal safety of those performing the repairs. Standard safety procedures and precautions (including use of safety goggles and proper tools and equipment) should be followed at all times to eliminate the possibility of personal injury or improper service which could damage the vehicle or compromise its safety.

Although this material has been prepared with the intent to provide reliable information, no warranty (express or implied) is made as to its accuracy or completeness. Neither is any liability assumed for loss or damage resulting from reliance on this material. SPECIFICALLY, NO WARRANTY OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR ANY OTHER WARRANTY IS MADE OR TO BE IMPLIED WITH RESPECT TO THIS MATERIAL. In no event will 3.0 Racing or its parent or affiliates be liable for any damages, direct or indirect, consequential or compensatory, arising out of the use of this material.

THE INFORMATION, PRODUCTS, MATERIALS AND SERVICES CONTAINED IN THIS DOCUMENT, INCLUDING WITHOUT LIMITATION, GRAPHICS, TEXT AND LINKS ARE PROVIDED ON AN "AS IS" BASIS WITH NO WARRANTY OF MERCHANTABILITY, FITNESS FOR A SPECIFIC USE OR REPRESENTATION OF ACCURACY.

LIMITATION OF LIABILITY

IN NO EVENT SHALL 3.0 Racing BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, PUNITIVE, CONSEQUENTIAL OR ANY OTHER DAMAGES WHATSOEVER, WHETHER IN ACTION OR UNDER CONTRACT, TORT OR OTHERWISE. Under no circumstance, including, but not limited to, negligence, shall 3.0 Racing be liable for any damages that result from the use of, or inability to use, the information, materials or products contained in or purchased from 3.0 Racing. Further, 3.0 Racing shall have no liability or responsibility for any delay in the delivery, installation or use of the products, as well as the service life of the products, performance, crash worthiness, applicability for the use intended, proper installation, or the accuracy of information provided.